

# Luxury Vinyl Tile

## Designer Outlet

CHARACTERISTICS	STANDARD	2.0/0.3mm	2.5/0.55mm	3.0/0.7mm
Type of floor covering	ISO 10582 (EN 649)	heterogeneous, PVC	heterogeneous, PVC	heterogeneous, PVC
Surface treatment		PUR	PUR	PUR
Total weight	ISO 23997 (EN 430)	3600 g/m <sup>2</sup>	4290 g/m <sup>2</sup>	5100 g/m <sup>2</sup>
Performance classification	ISO 10874 (EN 685)	23, 31	23, 33, 42	23, 34, 43
Gauge	ISO 24346 (EN 428)	2.0mm	2.5mm	3.0mm
Wear layer thickness	ISO 24340 (EN 429)	0.3mm	0.55mm	0.7mm
Dimensional stability	ISO 23999 (EN 434)	≤0.10%*	≤0.10%*	≤0.10%*
Residual indentation	ISO 24343-1	<0.05mm*	<0.05mm*	<0.05mm*
Light fastness	ISO 105-B02 (Method 3)	≥6	≥6	≥6
Reaction to fire	EN 13501-1	Class Bfl-S1	Class Bfl-S1	Class Bfl-S1
Slip resistance**	DIN 51130 EN 13893	R10 Class DS	R10 Class DS	R10 Class DS
Static electrical propensity	EN 1815	≤2.0 kV classified as 'antistatic'	≤2.0 kV classified as 'antistatic'	≤2.0 kV classified as 'antistatic'
Castor chair (continuous use)	ISO 4918 (EN 425)	Suitable	Suitable	Suitable
Underfloor heating		Suitable, max. 27°C	Suitable, max. 27°C	Suitable, max. 27°C
VOC emissions	AgBB/ABG	Very low emissions	Very low emissions	Very low emissions

\* Average test value from current production.

\*\* For clarification regarding slip, consult Polyflor technical services.

	PACK DIMENSIONS		
	2.0/0.3mm	2.5/0.55mm	3.0/0.7mm
Plank size	24 @ 152.4 x 914.4mm = 3.34m <sup>2</sup>	36 @ 101.6 x 914.4mm = 3.34m <sup>2</sup> 24 @ 152.4 x 914.4mm = 3.34m <sup>2</sup> 12 @ 304.8 x 914.4mm = 3.34m <sup>2</sup>	
Tile size	18 @ 304.8 x 609.6mm = 3.34m <sup>2</sup> 36 @ 304.8 x 304.8mm = 3.34m <sup>2</sup> 36 @ 152.4 x 609.6mm = 3.34m <sup>2</sup>	18 @ 304.8 x 609.6mm = 3.34m <sup>2</sup> 12 @ 304.8 x 914.4mm = 3.34m <sup>2</sup> 16 @ 457.2 x 457.2mm = 3.34m <sup>2</sup> 9 @ 609.6 x 609.6mm = 3.34m <sup>2</sup>  12 @ 152.4 x 609.6mm 2 @ 304.8 x 304.8mm 6 @ 304.8 x 609.6mm } = 3.34 m <sup>2</sup>	16 @ 457.2 x 457.2mm = 3.34m <sup>2</sup> 9 @ 609.6 x 609.6mm = 3.34m <sup>2</sup>

